

## LOAD BINDERS



If you're in a Bind, let Mid America Rigging help you out. We stock a variety of Lever Type and Ratchet Type Load Binders from the nation's top manufacturers. Below are some of our most popular Load Binders or you may [contact us](#) for additional types, sizes and availability.

## Lever Type Load Binder



- All components are forged, no cast parts
- Forged binders are lighter and stronger than cast binders
- Under equal force a forged handle will yield and bend while a cast handle may break

### LEVER TYPE LOAD BINDER

PRODUCT CODE	RATED LOAD	SIZE				HANDLE TAKE UP	WL LENGTH	WEIGHT
		G30	G43	G70	G80			
	(LBS)	(IN)	(IN)	(IN)	(IN)	(IN)	(IN)	(LBS)
48304	2,600	1/4	1/4	-	-	3.75	11.25	3.0
48304	5,400	3/8	3/8	5/16	-	4.50	16.12	8.1
48306	9,200	1/2	1/2	3/8	-	4.75	16.62	10.6
48769	7,100	3/8	3/8	3/8	3/8	4.50	16.62	8.1

## Claw Hook Load Binder



### Load binder operating instructions

1. Follow D.O.T. Federal Motor Carrier Safety Regulations S 392.9, S 393.100, and S 393.102
2. Inspect before use. Replace worn and deformed binders. Lubricate pivot and swivel points for optimum performance.
3. Do not operate with anyone on load.
4. Always apply lever binder in straight line hook to hook manner without bending and such that handle goes down when securing load.
5. Tighten binders before moving and recheck frequently.
6. Do not exceed working load limit shown on binder - hand effort will tighten binder to working load limit.
7. Do not use cheater bar or handle extension as their use can overload binder system and result in injury.
8. Secure handle down with a positive retaining method.
9. Release handle/load with extreme care. Make sure everyone is clear. Lever binder handle can snap back over center. Use open palm under handle and push up.

### CLAW HOOK LOAD BINDER

PRODUCT CODE	RATED LOAD	SIZE		HANDLE TAKE UP	WL LENGTH	WEIGHT
		G43	G70			
	(LBS)	(IN)	(IN)	(IN)	(IN)	(LBS)
SPECIAL ORDER	5,400	3/8	-	4.50	16.12	0.69
SPECIAL ORDER	9,200	-	3/8	4.75	16.62	1.00
SPECIAL ORDER	6,600	3/8	3/8	4.50	16.62	2.02

## Ratchet Type Load Binder



- Each ratchet component is forged from pure alloy steel
- Handle is designed loose using self-locking one-way bolts allowing easy removal of unwanted debris such as mud, snow or ice
- Proof tested to 50% of the minimum breaking strength
- Gears are permanently welded to the barrel

### RATCHET TYPE LOAD BINDER

PRODUCT CODE	END FITTINGS	RATED LOAD	SIZE					TAKE UP	HANDLE LENGTH	BARREL SIZE O. D.	SCREW DIA.	WEIGHT
			G30	G43	G70	G80	G100					
		(LBS)	(IN)	(IN)	(IN)	(IN)	(IN)	(IN)	(IN)	(LBS)	(LBS)	(LBS)
48364	HOOK/HOOK	2,600	1/4	1/4	-	-	-	4.00	11.00	1-5/16 X 6	3/4	5.4
48811	EYE/EYE (NO HOOK)	5,400	-	-	-	-	-	8.00	12.00	1-5/16 X 6	3/4	8.6
48363	EYE/EYE (NO HOOK)	13,000	-	-	-	-	-	8.00	14.00	1-1/2 X 10	1	9.8
46565	BODY ONLY	5,400	3/8	3/8	5/16	-	-	8.00	-	1-1/2 X 10	1	11.0
46566	BODY ONLY	9,200	1/2	1/2	3/8	-	-	8.00	-	1-1/2 X 10	1	11.7
46563H	HANDLE ONLY	-	-	-	-	-	-	-	14.00	-	-	4.3
48810	HOOK/HOOK	5,400	3/8	3/8	5/16	-	-	8.00	12.00	1-5/16 X 6	3/4	8.6
48360	HOOK/HOOK	7,100	3/8	3/8	3/8	3/8	-	8.00	14.00	1-1/2 X 10	1	13.0
48365	HOOK/HOOK	5,400	3/8	3/8	5/16	5/16	-	8.00	14.00	1-1/2 X 10	1	12.0
48366	HOOK/HOOK	9,200	1/2	1/2	3/8	3/8	-	8.00	14.00	1-1/2 X 10	1	13.0
48367	HOOK/HOOK	13,000	5/8	5/8	1/2	1/2	-	8.00	14.00	1-1/2 X 10	1	16.0
48458	HOOK/HOOK	12,000	-	1/2	1/2	1/2	-	8.00	14.00	1-1/2 X 10	1	13.0
48455	HOOK/HOOK	8,800	-	3/8	3/8	3/8	3/8	8.00	14.00	1-1/2 X 10	1	16.0

See also:

- [Specialty Lever Binders](#)
- [Specialty Forged Lever Load Binder](#)
- [E-Z Pro Cam Release Lever Binder](#)